

**BLUETOOTH LOW ENERGY**

# Wireless indoor air quality, temperature and humidity logger

SKU: 5906660327400



Wireless temperature, humidity and air quality logger is designed to monitor indoor climate conditions. The device measures air quality based on the concentration of volatile organic compounds (VOC) and calculates IAQ (Indoor Air Quality) representing air quality in the room based on the Bosch patented algorithm. Volatile organic compounds are substances derived from many indoor products, including from paints, cleaning agents, solvents, alcohol or glue. Some volatile organic compounds are carcinogenic. In addition, the sensor measures the temperature and relative humidity of air, which, in combination with the VOC concentration, gives a full picture of the room conditions.

## Key features

- **Works with Efento Cloud**  
Together with Efento Cloud, the sensors enable constant monitoring, alerting about exceeding safe limits, generating reports and analyzes.
- **Long battery life**  
Loggers have been designed to work for up to 5 years on battery. You can forget about changing the battery frequently or troublesome battery charging.
- **Lower costs**  
Choosing wireless sensors and a cloud platform reduces the installation and maintenance costs.
- **Wide range of sensors**  
Efento sensors can measure various physical and chemical values. If you decide on one sensor today, you can expand your sensors fleet to another types anytime you want.
- **Integration**  
Standard communication protocols allow integration with any cloud platform or mobile application.
- **Easy set up**  
All you need to set up a logger is a smartphone with a free mobile application. The whole configuration takes no more than 15 minutes.

## Technical data

### Air quality

- 0-500 IAQ - 0-50 - Good 51-100 - Average 101-150 - Little bad 151-200 - Bad 301-500 - Worse 500+ Very bad

### Temperature sensor

- Range: -40° to 125°C
- Accuracy up to 0.5°C in the range from -10°C to +85°C and up to 2°C in the range -55 to +125°C
- Resolution: 0.1°C
- Drift: <0.1°C / year
- Memory size: 40 000 measurements
- Measurement interval: 1 minute to 10 days, (configurable by the user)

### Humidity sensor

- Humidity: 0 to 100% RH
- Accuracy: 4% in the range of 0 to 80% and 7% in the range of 81 to 99%
- Memory size: 40 000 measurements
- Measurement interval: 1 minute to 10 days, (configurable by the user)

### Bluetooth Low Energy interface

- Communication: Bluetooth Low Energy (BLE)
- Radio module frequency: 2,4 GHz
- Power: 2,5 mW (4 dBm)
- Range: up to 100 m (LOS)
- Communication standard: Bluetooth Smart (Bluetooth Low Energy, Bluetooth 4.0)
- Transmission period: 1 s

### Battery

- Battery: 3,6 V, size AA, capacity 2 700 mAh (replaceable)
- Battery operating time: at least 5 years (measurement interval: 15 min)

### Mechanical

- Dimensions: 27 x 71 x 71 mm
- Weight: 80 g (including batteries)
- Enclosure: plastic ABS, color white
- Enclosure IP rating: IP30

### Environmental

- Operating
  - ◆ Temperature: -35° to 70°C
  - ◆ Humidity: 0 to 99 non-condensing
- Storage and transportation
  - ◆ Temperature: -40° to 70°C

## Additional information

### Calibration certificate

At the customer's request, each Efento sensor can be supplied with a calibration certificate in accordance with ISO / IEC 17025. The test is performed in an ILAC certified laboratory. The calibration date is saved in the logger's memory and it notifies the user about the suggested date of the next calibration.

### Data security

Data transmitted wirelessly between the sensor and smartphone / Efento Gateway can be encrypted. Thanks to that, unauthorized persons cannot hijack the communication between sensors and other devices. Efento sensors' software can be updated over the air, which will allow you to easily install any security patch that is released.

### Integration

If you want to integrate Efento loggers with your software, cloud platform or mobile application, we will provide you with the necessary documentation, libraries and / or SDKs.

### Sensor's passport

Sensor's passport documents the entire lifecycle of a device. By accessing the data on Efento Cloud platform, the user can check all information about the sensor: date of sale, warranty status, date of calibration, information on all service activities. In addition, the user can download all documents regarding the device – a duplicate of calibration certificate or service protocols.