



NB-IoT

Wireless illuminance logger

The Efento NB-IoT wireless data logger is designed for monitoring light intensity in applications requiring reliable data transmission. Using Narrowband IoT connectivity, it communicates directly over the cellular network. No gateways or additional infrastructure required.



Key Features

- **Effortless installation** - thanks to built-in NB-IoT connectivity, installation is as simple as mounting the device on a wall or placing it on a shelf - no gateways, cabling, or Wi-Fi configuration required.
- **Fast and intuitive setup** - with an integrated Bluetooth Low Energy (BLE) module and a dedicated mobile app, the sensor can be configured and activated in under 15 minutes.
- **Up to 8 years of battery life** - engineered for long-term, maintenance-free operation, the device uses intelligent data handling and optimized transmissions to achieve up to 8 years of operation on a single battery.
- **Cloud and system integration** - seamlessly connects with the Efento Cloud platform for data visualization, analysis, and alerting. Standard communication protocols also enable easy integration with custom server-based systems.
- **Remote management** - supports over-the-air firmware updates and secure remote configuration, reducing the need for on-site maintenance.
- **Instant notifications** - real-time alerts when thresholds are exceeded or anomalies are detected.

Applications

The device is designed for measuring light intensity in a monitored environment. It is ideal for use in offices, warehouses, production halls, greenhouses, museums, and smart building systems. It supports applications such as automatic lighting control, energy optimization, monitoring of working conditions, and protection of light-sensitive materials.

Sensors

Light

Model	Texas Instruments OPT3001DNPT
Measurement range	0-83 000 lx
Accuracy	+/- 10%
Resolution	0.1 lx
Filtering	rejects >99% IR (typical), spectral response matched to the human eye

Technical data

Data logging

Memory size	100 000 measurements
Measurement interval	5 s - 7 days (user-configurable)

Bluetooth interface

Radio module frequency	2.4 GHz
Power	2.5 mW (4 dBm)
Range	Up to 100 m (LOS)
Transmission period	1 s
Bluetooth version	Bluetooth Low Energy (4.0)

NB-IoT interface

NB-IoT bands	1, 2, 3, 4, 5, 8, 12, 13, 17, 18, 19, 20, 25, 26, 28, 66, 70, 71, 85
3GPP	13 i 14 (LTE Cat NB2)
Power	23 dBm ±2 dB

Communication

Protocol	CoAP
Transmission interval	1 min - 7 days (user-configurable)

Operating and Storage Conditions

Main unit operating conditions	Temperature: -25°C to +70°C, humidity: 0-99% RH (non-condensing)
Storage conditions	Temperature: -25°C to +70°C
Charging conditions (variants with external power supply)	Temperature: 0°C to +45°C

Certifications

Regulatory	CE (RED), FCC
Environmental	RoHS

Variants

EAN	Power Supply	Enclosure	Weight
5905309604353	8,500 mAh battery (replaceable). Battery life up to 8 years	IP30, white ABS plastic Dimensions: 32.5 × 60 × 125 mm	-
5905309604360	USB-C, with a 1,300 mAh rechargeable backup battery to maintain operation in case of power loss	IP30, white ABS plastic Dimensions: 32.5 × 60 × 125 mm	-